

UP-v3.1: editor cheat sheet

Shortcodes


UP allows you to give instructions in code or wysiwyg mode in an article or a personalized module using shortcodes.

```
{up action=paramètre principal | option=valeur de l'option}
```

- an "opening" shortcode always starts with **up** (altGr+4 followed by the word up)
- followed by a space and the name of the action to be performed: **action**
- if the action expects a **main parameter**, it is indicated after the equal sign
- it is possible to indicate several options by separating them with the **pipe** character (altGr+6).
- it always ends with a closing brace (altGr+=)

Certain actions allow you to enter content in the usual way following the shortcode. We indicate the end of this content by a **"closing" shortcode** where the word **up** is preceded by a backslash followed by the name of the action (identical to that of the opening shortcode):

```
{/up action commentaire_optionnel}
```



- the **shortcode** can be on several lines for easier reading
- the **name of actions and options** is not min/shift sensitive.
The hyphen and underscore have the same meaning.
- the **names of stocks and options** may have synonyms. They are indicated in parentheses in the action documentation
- an **option without an argument** is considered true or 1. 0=False
- the **argument of an option and/or the content** may contain another UP action
- **whitespace (starting and ending)** of an argument is removed, unless surrounded by double quotes.

Separator shortcodes

they are used to isolate different parts of the content between the opening and closing shortcode. This method is more visual and makes it easier to enter in an editor like TinyMCE or JCE

```
{up filter | guest} vous êtes invité {===} vous êtes identifié {/up filter}  
{up flexauto=2} bloc 1 {=== commentaire} bloc 2 {/up flexauto}
```

To be recognized, a separator must start with a curly brace followed by 3 equal signs and end with a curly brace.
It is allowed to add a comment before the closing brace {===== comment}

Internal or secondary shortcodes

Used to provide optional information, they are inserted between the opening and closing shortcodes. They **don't start** with up. See the documentation for the actions concerned.

```
{up osmap=48.865, 2.30}  
{marker=48.8709, 2.33223 | popup-text=... }  
{/up osmap}
```

Shortcodes as argument

It is possible to put the shortcode of an action as content or as an argument for the option of another action.

Actions are evaluated starting from the end of the article and most included first.

```
1 {up table-par-Lignes} ④  
2 {up csv2table | header=id;titre} ③  
3 {up jnews=8 ②  
4 | main-tag=0 | item-tag=0  
5 | template=##id##;##title##  
6 | new-html={up icon=etoile} ①  
7 }  
8 {/up csv2table}  
{/up table-par-Lignes}
```

The actions are autonomous and independent. They must return content that is compatible with the parent action.

This can cause problems when a child action adds code directly to the head. In this case, use the action's filter option.

Warning It is not possible to put shortcodes as an argument of an option in the prefs.ini file

Translation

option=Lang[en=YES;fr=OUI] allows you to offer alternatives depending on the visitor's language. If its language is not specified, we use the first option.

The **lang** action can be used except in the prefs.ini file

Date format

%y : AA, %Y : YYYY, %m : 01-12, %b : month 3 letters, %B : name month, %d : 01-31, %e : 1-31, %a : daysem 3 letters, %A : weekday, %U : Week number, %l : hour (1-12) AM/PM - L min, %I : hour (01-12) AM/PM - i maj, %k :hour (0-23), %H : hour (00-23), %P : am/pm, %p : AM/P M, %M : minute (00-59)

BBCode

To **enter HTML code understood by UP**, but ignored by editors.
You have to replace them <> with brackets []. Example: [b]gras[/b]
To insert a bracket, you must escape it with a backslash \[
Only the most common tags are supported:

```
a|br|p|h3..6|div|span|b|i|u|img|small|sup|sub|quote|ul|ol|li|code|tt|kbd
```

Common options

option=1 or **option** (without argument) are considered true, **option=0** is considered false.
id : identifier of the main block of the action. UP creates it automatically, but you can force it if you need to reuse it for another action (ex: addcsshead)
? : displays a summary of the commands and action in the user's language as well as the presets defined by the webmaster.

debug : displays the list of options with current values. Those by default and those entered in the shortcode. At the end of the message, you will find the list of presets defined for your site.

prefset : allows you to apply a set of options with an explicit and easy-to-remember name. An option set (prefset) can also be called as an argument to the main option. and produce the same result. {up hr=param} {up hr | prefset=param}

style, **class** : CSS properties or class name(s) for the main block of the action. UP accepts mixing class names and CSS properties: class=color:red;bg-yellow is valid. Braces are prohibited inside the shortcode. To indicate the CSS rule, we write [a[title][color:red]a\[title\]][color:red]

xxx-style, **xxx-class** : CSS properties or class name(s) for the indicated element (eg: title-class).

xxx-style-*, **xxx-class-*** : default style and class for all elements. example: col-cClass-=t-bleu all columns of the table in blue.: col-cClass-6=t-rouge the 6th column in red. 12 elements maximum.

css-head : adds CSS rules to the head of the page. example: css-head=body[background:pink] #id a[text-decoration:underline] \[cClass="foo"\][color:red] curly braces {} are replaced by square brackets []. #id, will be replaced by the action identifier. To enter a hook, escape it with a backslash.

filter : does not execute the action if one of the conditions is false. example: the exclamation point reverses the meaning of the condition filter=motClé:condition;!motClé:condition;...

datemax true until this date (YYYYMMDDHHMM) **datemin** true from this date (YYYYMMDDHHMM) **period** true between these dates (if year omitted, test for current year) (YYYYMMDDHHMM, YYYYMMDDHHMM) **day** list of authorized days (1.7 -> Monday or Sunday) **month** list of authorized months (1.2 -> January or February) **hmax** true until this time (HHMM) **hmin** true from this time (HHMM) **hperiod** true between these time slots (possible list) (HHMM-HHMM) **guest** true if unidentified user **admin** true if admin **user** list of authorized usersids (8,12) **username** list of authorized usernames (admin,lomart) **group** list of authorized usergroups (8,12) **lang** list of authorized languages. (fr,ca) **mobile** true if displayed on mobile **homepage** true if home page **server-host** true if argument appears in the name of the host server (ex: server-host:lomart.fr (a subdomain of lomart. fr) **server-ip** true if IP in the list (localhost, ::1, 192.168.0.1)

Help and support

If you add a **question mark** or the word **debug** as an option to the shortcode, UP will display help at the beginning of the page on the site.

Common errors

- The **shortcode is visible on the generated page.**
 - the plugin is not activated
 - space between the brace and the word up
 - the brace is in bold. Classic after copying and pasting from this site
 - in a custom module without support for content plugins
 - the **shortcode doesn't seem to work**
 - forgetting the slash in front of the up of the closing shortcode
 - the name of the action in the closing shortcode is different from that in the opening shortcode
 - message: content not found**
 - the closing shortcode is incorrect
 - options are not taken into account**
 - colon (instead of equal sign) as parameter/value separator. UP should notify you with a message indicating that it does not know about the option. If in doubt, consider adding debug in the options to find out what UP includes!
 - weird behavior**
 - perhaps an unintentional addition of HTML tag during copy and paste or by the editor (check in code mode). Normally, UP cleans up unnecessary tags before passing the info to the action.
 - With a wysiwyg editor, the opening shortcode is in a P tag and the closing one in a DIV tag
- UP does not recognize this option: =1**
- you have one extra pipe character (alt-gr+6) in the shortcode